

# AAA TECHNOLOGY & SPECIALTIES CO., INC.

## DOUBLE SUSPENSION                      D TYPE

(For Sizes 67 through 74)

### PHYSICAL DIMENSIONS

Rod Take-out = A\* - K

SIZE	TOTAL TRAVEL (IN)	STD. ROD DIA. (IN)	B (IN)	E (IN)	F (IN)	G (IN)	H (IN)	J (IN)	K (IN)	M (IN)	Q (IN)	U (IN)	Z (IN)	APPROX. WEIGHT (LBS.)	
														NET	SHIPPING
75	7 - 20	2 1/2 - 4	23 15/16	47	9 1/2	27	3 5/8	1 1/4	3 x Rod Dia. (Min.)	18	5	2 3/4	5	5300	5600
76	7 - 20	2 1/2 - 4 1/4	23 15/16	50	9 1/2	27	3 5/8	1 1/4		18	5	2 3/4	5	5700	6000
77	7 1/2 - 20	2 3/4 - 4 1/4	23 15/16	51 1/8	9 1/2	27	3 5/8	1 1/4		18	5	2 3/4	5	5720	6020
78	8 - 20	2 3/4 - 4 1/4	23 15/16	55 1/8	9 7/8	27	3 5/8	1 1/4		16	5	2 3/4	5	5800	6100
79	9 - 20	3 - 4 1/4	23 15/16	58 1/4	9 7/8	27	3 5/8	1 1/4		16	5	2 3/4	5	6400	6750
80	10 - 20	3 1/4 - 4 1/4	23 15/16	53 3/8	10 5/8	27	3 5/8	1 1/4		16	5	2 3/4	5	6670	6980
81	11 - 20	3 1/4 - 4 1/4	26 15/16	54 5/8	10 5/8	30	3 5/8	1 1/2		19	5	2 3/4	5	6950	7300

### DIMENSION "Y"

ROD DIA.	2 1/2	2 3/4	3	3 1/4	3 1/2	3 3/4	4	4 1/4
75 - 80	8	8	9	9	10	10	11	11
81	8 1/2	8 1/2	9 1/2	9 1/2	11	11	12	12

For Load Rod Capacities See Page 3